



Americrete, Inc.  
41730 Reagan Way  
Murrieta, Ca 92562  
Toll Free (800) 775-8880  
Technical Help (800) 775 -8880

## Material Safety Data Sheet A-7300 Part B

Date of Preparation: 01/15/04

### SECTION 1 - MATERIAL IDENTIFICATION

PRODUCT NAME Crack Repair

PRODUCT CODE A-7300 Part B

### EMERGENCY OVERVIEW

HMIS HEALTH RATING 3 FLAMMABILITY 1 REACTIVITY 0  
PHYSICAL FORM MOBILE LIQUID  
COLOR STRAW YELLOW  
ODOR AMINE  
HAZARDS HARMFUL IF IN CONTACT WITH SKIN. CORROSIVE TO EYES.  
CORROSIVE TO SKIN. SEVERE EYE IRRITANT. SEVERE SKIN  
IRRITANT. MAY CAUSE SKIN SENSITIZATION.  
EXTINGUISHING MEDIA Ignition will give rise to a Class B fire. In case of large fire use:  
Alcohol Foam, Water Spray. In case of small fire use: Carbon  
Dioxide (CO<sub>2</sub>), Dry Chemical, Dry sand or limestone.

C.A.S. CHEMICAL NAME Mixture  
SYNONYMS None  
CHEMICAL FAMILY Aliphatic Amine  
EMPIRICAL FORMULA Mixture  
INTENDED USE Curing Agent, Epoxy

### SECTION 2 - INGREDIENTS

#	WT %	CAS Number and Chemical Name
1.	<45.00	25154-52-3 NONYLPHENOL
2.	<10.00	1761-71-3 methylenebiscyclohexanamine,4,4'-

The remaining components are trade secret.

**OSHA (ACGIH) Exposure Limits**

	TWA ppm	mg/m3	ppm	STEL mg/m3	ppm	CEILING mg/m3	
1. OSHA	N/E	N/E		N/E	N/E	N/E	N/E
ACGIH	N/E	N/E		N/E	N/E	N/E	N/E
2. OSHA	N/E	N/E		N/E	N/E	N/E	N/E
ACGIH	N/E	N/E		N/E	N/E	N/E	N/E

N/E = Not Established.

**SECTION 3 - HEALTH HAZARDS**

**ROUTES OF EXPOSURE**

Eye Contact  
Skin Contact  
Ingestion  
Skin Absorption

**EXPOSURE STANDARDS**

No standards established for the product. Maintain air contaminant concentrations in the workplace at the lowest feasible levels.

**HEALTH HAZARDS**

Harmful if in contact with skin.  
Corrosive to eyes.  
Corrosive to skin.  
Severe eye irritant.  
Severe skin irritant.

May cause skin sensitization.

**TARGET ORGANS**

Eye  
Skin

**SIGNS AND SYMPTOMS OF EXPOSURE (Acute effects)**

Product vapor in low concentrations can cause lacrimation, conjunctivitis and corneal edema when absorbed into the tissue of the eye from the atmosphere. Corneal edema may give rise to a perception of 'blue haze' or 'fog' around lights. The effect is transient and has no known residual effect. Burns of the eye may cause blindness. Contact of undiluted product with the eyes or skin quickly causes severe irritation and pain and may cause burns, necrosis and permanent injury. Inhalation of aerosols and mists may severely damage contacted tissue and produce scarring. Risk of exposure to hazardous concentrations of vapor under normal working conditions in a well ventilated space is minimal. However, conditions such as spraying, or sudden release of hot liquid, which generate an aerosol, mists or fog should be avoided. Ingestion may cause death unless treated promptly. Product is readily absorbed through the skin and may cause malaise, discomfort, injury, and death unless treated promptly.

**SIGNS AND SYMPTOMS OF EXPOSURE (Possible Longer Term Effects)**

Repeated and/or prolonged exposure may cause allergic reaction/sensitization. Repeated and/or prolonged exposures may result in: adverse eye effects (such as conjunctivitis or corneal damage), adverse skin

effects (such as rash, irritation or corrosion).

#### **MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Eye disease

Skin disorders and Allergies

#### **CARCINOGENS UNDER OSHA, ACGIH, NTP, IARC, OTHER**

This product contains no carcinogens in concentrations of 0.1 percent or greater.

---

#### **SECTION 4 - FIRST AID**

---

##### **EYE CONTACT**

Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice.

##### **SKIN CONTACT**

Remove product and immediately flush affected area with water for at least 15 minutes. Remove contaminated clothing and shoes. Destroy contaminated leather apparel. Cover the affected are with a sterile dressing or clean sheeting and transport for medical care. **DO NOT APPLY GREASES OR OINTMENTS.** Control shock, if present. Launder contaminated clothing prior to reuse.

##### **INHALATION**

Move patient to fresh air. If breathing has stopped or is labored give assisted respiration (e.g. mouth-to-mouth). Prevent aspiration of vomit. Turn victim's head to the side. Seek medical advice.

##### **INGESTION**

In the event of ingestion, administer 3-4 glasses of milk or water. **DO NOT INDUCE VOMITING.** Seek medical advice.

---

#### **SECTION 5 - FIRE AND EXPLOSION DATA**

---

**FLASH POINT (closed cup) 150.56 C (303.01 F)**

**UPPER EXPLOSION LIMIT (UEL) No Data**

**LOWER EXPLOSION LIMIT (LEL) No Data**

**AUTOIGNITION TEMPERATURE No Data**

**FIRE HAZARD CLASSIFICATION (OSHA/NFPA)**

**Class IIIB**

##### **EXTINGUISHING MEDIA**

Ignition will give rise to a Class B fire. In case of large fire use: Water Spray, Alcohol Foam. In case of small fire use: Carbon Dioxide (CO<sub>2</sub>), Dry Chemical, Dry sand or limestone.

##### **SPECIAL FIRE FIGHTING PROCEDURES**

A face shield should be worn. Firefighters should wear butyl rubber boots, gloves, and body suit and a self-contained breathing apparatus. Retain expended liquids from fire fighting for later disposal.

##### **UNUSUAL FIRE AND EXPLOSION HAZARDS**

May generate toxic or irritating combustion products. May generate carbon monoxide gas. May generate toxic nitrogen oxide gases. May generate ammonia gas. Personnel in vicinity and downwind should be evacuated.

---

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

---

**CONTAINMENT TECHNIQUES (Removal of ignition sources, diking etc)**

Stop the leak, if possible. Reduce vapor spreading with a water spray. Shut off or remove all ignition sources. Construct a dike to prevent spreading.

**CLEAN-UP PROCEDURES**

If recovery is not feasible, admix with dry soil, sand or non-reactive absorbent (sodium bisulfate) and place in a container or dumpster pending disposal. Transfer to containers by suction, preparatory for later disposal. Flush area with water spray. Clean-up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. For large spills, recover spilled material with a vacuum truck.

**OTHER EMERGENCY ADVICE**

Wear protective clothing, boots, gloves, and eye protection.

---

**SECTION 7 - HANDLING AND STORAGE**

---

**STORAGE**

Keep away from acids and oxidizers. Keep in cool, dry, ventilated storage and in closed containers. Do not store in iron or other reactive metal containers.

**HANDLING**

Avoid contact with skin or eyes. When handling, do not eat, drink, or smoke.

**OTHER PRECAUTIONS**

Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations (e.g. OSHA).

---

**SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS**

---

**EYE PROTECTION**

Full face shield with goggles underneath.

**HAND PROTECTION**

Neoprene rubber gloves. Impermeable gloves. Cuffed butyl rubber gloves. Nitrile rubber gloves.

**RESPIRATORY PROTECTION**

Not required under normal conditions in a well-ventilated workplace. At elevated temperatures a cartridge mask National Institute for Occupational Safety and Health (NIOSH) approved for ammonia may be appropriate.

**PROTECTIVE CLOTHING**

Impervious clothing. Slicker suit. Rubber boots. Full rubber suit (rain gear). Butyl or latex protective clothing.

**ENGINEERING CONTROLS**

No specific controls needed.

## WORK AND HYGIENIC PRACTICES

Provide readily accessible eye wash stations and safety showers. Was at the end of each

workshift and before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Discard contaminated leather articles. Launder or discard contaminated clothing.

---

## SECTION 9 - TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

---

Physical Form	Mobile Liquid
Color	Straw Yellow
Odor	Amine
pH	Alkaline
Vapor Pressure (mm. Hg. at 21C (70C))	<2.00
Vapor Density (Air = 1)	No Data
Boiling Point	> 222.00 C (>431.60 F)
Solubility in Water	Slight (0.1 - 1%)
Specific Gravity (Water=1)	0.98
Molecular Weight	Mixture

---

## SECTION 10 - STABILITY AND REACTIVITY

---

### CHEMICAL STABILITY

Stable.

### CONDITIONS TO AVOID (if unstable)

Not applicable.

### INCOMPATIBILITY (Materials to Avoid)

Mineral acids (i.e. sulfuric, phosphoric, etc.). Organic acids (i.e. acetic acid, citric acid, etc.). Oxidizing Agents (i.e. perchlorates, nitrates etc.). Reactive metals (i.e. sodium, calcium, zinc etc.). Sodium or Calcium Hypochlorite. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Materials reactive with hydroxyl compounds. A reaction accompanied by large heat release occurs when the product is mixed with acids. Heat generated may be sufficient to cause vigorous boiling creating a hazard due to splashing or splattering of hot material.

### HAZARDOUS DECOMPOSITION PRODUCTS (from burning, heating, or reaction with other materials).

Carbon Monoxide in a fire. Carbon Dioxide in a fire. Ammonia when heated. Nitrogen Oxides in a fire. Irritating and toxic fumes at elevated temperatures. Nitric acid in a fire. Aldehydes. Nitrogen oxide can react with water vapors to form corrosive nitric acid (TLV=2 ppm).

### HAZARDOUS POLYMERIZATION

Will not occur

### CONDITIONS TO AVOID (if polymerization may occur)

Not applicable

---

## SECTION 11 - TOXICOLOGICAL PROPERTIES

---

### ACUTE ORAL TOXICITY (LD50, RAT)

>1620.00 mg/kg (Estimate)

**ACUTE DERMAL TOXICITY (LD50, RABBIT)**  
>1000.00 mg/kg (Estimate)

**ACUTE INHALATION TOXICITY (LC50, RAT)**  
> 10.00 mg/L / 1 hr (No deaths) (Estimate)

**MISCELLANEOUS TOXICITY DATA**  
Data available on components only.

**OTHER ACUTE EFFECTS**  
No Data

**IRRITATION EFFECTS DATA**  
Irritation data based on estimates.

**CHRONIC/SUBCHRONIC DATA**  
No delayed, subchronic or chronic test data are known.

---

**SECTION 12 - ECOLOGICAL INFORMATION**

---

No Data

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

---

**WASTE DISPOSAL**  
Comply with all Federal, State and Local Regulations.

---

**SECTION 14- TRANSPORT INFORMATION**

---

**DOT NON-BULK SHIPPING NAME** Amines, liquid, corrosive, n.o.s.  
(METHYLENEBISCYCLOHEXANAMINE, 4,4'-)  
// 8 // UN2735 // PG II

**IMO SHIPPING DATA** Amines, liquid, corrosive, n.o.s.  
(METHYLENEBISCYCLOHEXANAMINE, 4,4'-)  
// 8 // UN 2735 // II // Marine Pollutant  
(NONYLPHENOL) // IMDG Page 8109-2 // F.P.  
150.6 C // Placarded Corrosive // HazMat  
STCC=4935601 // EmS No: 8-05 // MFAG No: 320

**ICAO/IATA SHIPPING DATA** Amines, liquid, corrosive, n.o.s.  
(METHYLENEBISCYCLOHEXANAMINE, 4,4'-)  
// 8 // UN 2735 // II // F.P. 150.6 C // Shipment per  
49 CFR 171.11

---

**SECTION 15 - REGULATORY INFORMATION**

---

**US FEDERAL REGULATIONS**

MSDS 7300 Part B

**TOXIC SUBSTANCES CONTROL ACT (TSCA)-**

All components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**OSHA Hazard Communication Standard (29CFR1910.1200) hazard class(es)**  
Corrosive. Sensitizer

**EPA SARA Title III Section 312 (40CFR370) hazard class**  
Immediate Health Hazard. Delayed Health Hazard.

**EPA SARA Title III Section 313 (40CFR372) toxic chemical above "de minimis" level are**  
None

**STATE REGULATIONS**

**PROPOSITION 65 SUBSTANCES (component(s) known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986")**  
None

**NEW JERSEY TRADE SECRET REGISTRY NUMBER(S)**  
05995500-(H239OU)

---

**SECTION 16 - INTERNATIONAL REGULATIONS**

---

**CANADA**

**DSL**

Not on Inventory.

**WHMIS HAZARD CLASSIFICATION**

Class D Division 2B, Class E Corrosive,

**WHMIS TRADE SECRET REGISTRY NUMBER(S)**

Not applicable

**WHMIS SYMBOLS**

Test tube/hand, Stylized T,

**EUROPEAN ECONOMIC COMMUNITY (EEC)**

**EINECS MASTER INVENTORY**

Not on Inventory

**EEC SYMBOL**

**CORROSIVE (C)**

**EEC RISK (R) PHRASES**

Harmful if swallowed (R22). Causes burns (R34). May cause sensitization by skin contact (R43).

**EEC SAFETY PHRASES**

Do not breathe fumes (S23). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26). Wear suitable protective clothing, gloves and eye/face protection (S36/37/39). In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

