



Americrete, Inc.
41730 Reagan Way
Murrieta, Ca 92562
Toll Free (800) 775-8880
Technical Help (800) 775-8880

Material Safety Data Sheet A-900

Emergency Assistance

For Chemical Emergency Spill, Leak, Fire or Exposure call 24 hours a day: **CHEMTREC** (800) 424-9300. Outside U.S. call (703) 527-3887. Collect calls accepted.

SECTION I PRODUCT IDENTIFICATION

Product Name: Gray-Waterproofing Base Coat A-900
Product Class: Dry Co-Polymer Emulsion mixed with different size sand and Portland cement.

HMIS Rating: Health 1 Fire 0 Reactivity 0
0=Least, 1=Slight, 2=Moderate, 3=High, 4=Extreme

SECTION II PHYSICAL DATA

Appearance: Cement Gray
Odor Characteristic: Ester/acetic Odor
Specific Gravity: 3.10
Vapor Density: N/A
Solubility in Water: Dilutable
Evaporation Rate: N/A

SECTION III FIRE AND EXPLOSION HAZARD DATA

Flammability Class: N/A«flammabilityclass»
Flash Point: N/A
LEL: N/A
Extinguishing Media: Water, CO2 or Dry Chemical
Unusual Fire and Explosive Procedures: Wear Self-contained breathing apparatus

SECTION IV HEALTH HAZARD DATA

Permissible Exposure Level: The ACGIH TLV and OSHA PEL for vinyl acetate are both set at 100ppm for an 8 hour TWA and at 20 ppm for the STEL
Effects of Overexposure:

- Inhalation: Headache, nausea, irritation of the nose, throat and lungs, vomiting
- Skin Contact: May cause slight irritation

- Eye Contact May cause irritation
- Ingestion Cause nausea, dizziness and vomiting

Medical Conditions prone to Aggravation by overexposure: May cause irritation to respiratory tract.

Primary Route(s) of Entry: Inhalation, eye. Ingestion is not a normal hazard in industrial use.

Emergency First Aid Procedures:

- Inhalation overexposure: Move to fresh air. If breathing stops, give artificial respiration and seek immediate medical attention.
- Eye Contact: Flush with large quantities of water for 15 minutes and seek medical attention.
- Skin Contact: Wash thoroughly with soap and water immediately.
- Ingestion: Do not induce vomiting. Obtain medical treatment immediately.

Toxicological Information and Long Term Effects of Overexposure:

Product contains residual vinyl acetate monomer (108-05-4), an IARC 2B possible human carcinogen. Vinyl acetate vapors have been shown to cause tumors in the respiratory tract of laboratory animals exposed to 600 ppm over a lifetime: 200ppm causes irritation. 50 ppm produces no observable effects. There is no evidence of adverse effects to humans exposed to levels at or below the AGCGIH TLV.

SECTION V REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: Combustion may yield yellow carbon monoxide and/or carbon dioxide and traces of monomer and low levels of organic volatiles.

Conditions to Avoid: Keep from freezing

Incompatibility (Materials to Avoid): None Known

SECTION VI SPILL OF LEAK PROCEDURES

Steps to take if material is released or spilled: Use dry cleanup methods that do not disperse the dust into the air.

Waste disposal Method: Material can be returned to container for later use if not contaminated, can be disposed of as an industrial waste, mixed with water and discarded as a concrete product.

SECTION VII SAFE HANDLING AND USE INFORMATION

Respiratory Protection: When spraying, use a NIOSH approved cartridge respirator to keep airborne mists vapor concentrations below the time weighted threshold limit values. When using in poorly ventilated areas, use a fresh air supplying respirator or a self-contained breathing apparatus.

Ventilation: General mechanical ventilation or local. Exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

Protective Gloves: Impermeable chemical gloves for skin protection.

Hygienic Practices: Eye washes and safety showers are recommended in the work place.

SECTION VIII SPECIAL PRECAUTIONS

Handling and Storage: Do not store in temperatures over 120 degrees F. Product contains low levels of organic volatile which may build up on unvented head space of storage carton. Ventilate sufficiently to keep limits of exposure below TLV's.

Other Precautions: Product may be damaged if allowed to freeze.

REGULATORY INFORMATION

Transportation: Not regulated by US DOT

Chemical Control Laws: All components of this product are listed or are excluded release reporting under section 33 Vinyl acetate (108-05-04).

State Right-to-Know Laws: Any material listed as “not hazardous” in the CAS column of the ingredient information section of this MSDS is trade secret under the provisions of the Pennsylvania worker and community right-to-know act.

California Prop 65: This product contains trace amounts of a component or components known to the state of California to cause cancer: Acrylamide (79-06-1) <0.1%, and Acetaldehyde (75-07-0) <0.1%