



Flex Mesh

A-1620/A-1625/A-1630

Product Description

Flex Mesh A-1620/A-1625/A-1630 is a reinforced, Heavy gauge alkali resistant nylon netting used in Americrete's A-16,000 Waterproofing Deck Systems (See Americrete's Specification A-16,000) and can also be used for Crack Repair for areas that may need a stronger repair (See Americrete's Specification A-17,000).

Coverage Rate

A-1620/A-1625/A-1630 Flex Mesh comes in two sizes: **A-1620** is a 3" x 150' roll with a **sticky** back, which will yield 150 linear feet. **A-1625** is a 36" x 150' roll which will yield 450 square feet. **A-1630** is a 36" x 150' roll with a **sticky** back which will yield 450 square feet.

Primary Uses

Americrete A-1620/A-1625/A-1630 Flex Mesh is primarily used to help stop cracks from telegraphing through Americrete's decorative concrete coatings over concrete or plywood.

Application

When using A-1620/A-1625/A-1630 with A-16,000 or A-9000 specification, the A-900 base coat **must** be completely dry. Apply A-1620/A-1625/A-1630 Flex Mesh with sticky side down and roll A-8100 Waterproofing bonder over the top with a paint roller. Allow to dry before continuing. When using A-1620 for crack repair, apply A-600 over dry, pre-filled cracks with the mixture of A-900 and A-400 and embed A-1620 into the wet A-600, press down with a trowel. Note: An additional coat of A-600 may need to be applied in order to completely cover the A-1620 Flex Mesh. See Specification A-17,000 Cementitious Crack Repair System for complete crack repair directions.

Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification