



**Americrete**<sup>Inc</sup>  
MANUFACTURER OF DECORATIVE OVERLAYS & SEALERS

# High Shine Accelerator

## A-1550

### Product Description

A-1550 High Shine Accelerator is an oil based product designed to speed up drying time when using A-1400 High Shine or A-1450 High Shine Plus.

#### Coverage Rate

A-1550 comes in a 2 ounce tube designed to treat 2 gallons of either A-1400 High Shine or A-1450 High Shine Plus.

#### Primary Uses

A-1550 is primarily used in cold weather, indoors or in shaded areas where conditions may prolong the drying time of A-1400 or A-1450 sealers.

#### Application

One 2-ounce tube of A-1500 should always be used **one ounce per gallon of sealer at a time**. Never treat more than 1 gallon of High Shine or High Shine Plus at a time. If there is any material left with A-1550 mixed in it, the shelf life will be reduced and the sealer may not be able to be used in the future.

#### Limitations

Not recommended for application below 28 degrees F. Do not apply on wet or damp surfaces. Do not allow to puddle or apply thick coats. Americrete Integral Beads A-1402 can be added to the product to produce an anti-skid surface. When applying this product, the applicator (and everyone in the immediate area) must wear protective clothing such as a filtered mask, gloves, boots, long sleeve shirt, long pants, as well as proper eye protection.

#### Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.