



# Stamp Crete A-700 (White)

## Product Description

A-700 Stamp Crete is a proprietary mixture of specially modified acrylic co-polymer resins mixed with various sized aggregates. Stamp Crete is formulated to achieve 1/4 inch to 3/8 inch thickness profile that can be stamped using templates to achieve a simulated appearance of slate, brick, stone, or other designs. Stamp Crete is approved over Americrete waterproofing base coat. Available in gray.

**Note:** Stamp Crete Primer must be used prior to Stamp Crete. Stamp Crete must be applied into wet primer A-750. Stamp Crete Primer is applied over wet concrete only.

## Coverage Rate

A-700 Stamp Crete will cover approximately 25 square feet per bag. A-700 Stamp Crete maintains a 1/4 inch to 3/8 inch profile for stamping.

## Primary Uses

A-700 Stamp Crete eliminates concrete removal, and is used to create over many designs and textures. Color selection is unlimited with Americrete Concrete Stains. A-700 Stamp Crete System is UV resistant, water repellent, petroleum and stain resistant. Stamp Crete penetrates the surface for a tenacious bond. Stamp Crete is a one component mix, by just adding water. This product is easy to maintain, and will resist tire marks. Stamp Crete is environmentally friendly.. See specification A-7000 for complete installation instructions.

## Typical Applications

Interior and exterior floors, malls, casinos, amusement parks, walkways, driveways, pavilions, pool decks, stairs and landings, patios and decks, showrooms and many more.  
See Specification A-7000.

Note: On vertical surfaces stamp crete or Wall Stamp may be used.

## Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.