



Americrete^{Inc}

MANUFACTURER OF DECORATIVE OVERLAYS & SEALERS

Asphalt Spall Repair Product AR-625CT – Cal Trans Patent Pending AR-375 Included

Product Description

Asphalt Concrete Spall Repair is a powdered proprietary co-polymer patching compound that is easy to install for large projects or small repairs in asphalt concrete. Concrete Asphalt and Concrete Spall Repair is extremely easy to apply and mixes with 1 gallon of **AR-375** Admix and 2 quarts of water. It also dries rapidly due to our special ingredients to allow traffic to drive on the surface normally within 30 to 45 minutes. Overlay products can be applied over the **AR-625CT** much faster and more effectively due its quick drying time.

Coverage Rate

The rate of coverage for the Asphalt Spall Repair Product will vary with the size, depth and width of the spall to be repaired. Before application of the product, the area needs to be primed with Americrete's Concrete Bonder Admix **AR-300**.

Primary Uses

When sufficient aggregate is applied onto the wet surface, AR-625CT will meet or exceed Cal Trans coefficient of friction test of 0.35. Americrete Spall Repair's primary uses are to repair spalled areas in asphalt, bridges, roadways, concrete, curbs and gutters, and anywhere there is a spalled area in need of repair. **Environmentally Friendly.**

Application

Apply one gallon of **AR-375** to one bag of **AR-625CT**. Add 1 to 2 quarts of water at a time until desired consistency is achieved. Apply product at once. The mixture dries rapidly. *Note: mixing should be done at the area site.*

Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.