

Graffiti Deterrent

GS-100

Product Description

Graff Shield's GS-100 Deterrent is a water base clear polymer designed to water proof substrates with incredible adhesion qualities. GS-100 Deterrent is a non hazardous, environmentally friendly, non yellowing, biodegradable, and cleans up only with water.

Primary Uses

Masonry block, split face block, brick, metal, concrete, wood, stucco, siding, vinyl, etc.

Application Equipment

Hand held pump sprayer or airless machine and/or a broom for porous surfaces.

Application

Be sure the surface is clean before applying GS-100 Graffiti Deterrent.

Apply GS-100 to the surface to be protected with a pump-up or airless sprayer starting at the bottom of the wall or substrate and working up to the top of the area to be covered. Allow GS-100 Deterrent to dry before applying GS-200 Graffiti Lift. For porous block or substrates, take a soft broom and agitate the GS-100 evenly into the substrate. Note: It is mandatory to apply GS-200 Graffiti Lift over the entire surface. Note: For better results, apply 2 coats of GS-200 Graffiti Lift.

Coverage Rate

Porous surfaces: (split face block) 250 – 350 square feet per gallon, two coats may be required.

Smooth surfaces: 300 – 400 square feet per gallon.

Packaging

1 Gallon Jug, 5 Gallon Bucket and 55 Gallon Drum.

Caution

This product may cause burns upon prolonged exposure. Harmful if swallowed. In case of contact with eyes or skin, flush with water for 15 minutes and obtain medical attention. Before using this material, read material safety data sheets. Always wear protective clothing and eye protection when using GS-100. Wash your hands after using product. Keep away from children.

First Aid

If ingested, seek medical attention immediately. In case of eye contact, flush with water for 15 minutes. In case of skin contact, wash thoroughly with soap and water. If irritation occurs, seek medical attention.

Warranty

Graff Shield, Inc. warrants that this product is blended to the highest quality. This warranty is only for replacement of material and only if the material that was applied was documented by either a Graff Shield, Inc. representative and/or by an agent or certified applicator of Graff Shield, Inc. products. This can also be done by video taping the installation.

The Graff Shield, Inc. anti-graffiti system must be applied by using GS-100 Graffiti Deterrent in conjunction with GS-200 Graffiti Lift at a rate of 300 square feet per gallon. Every time graffiti is removed, an additional coat of GS-200 Graffiti Lift **must** be re-applied for this warranty to be valid. To

remove graffiti markings, apply GS-300 Graffiti Eliminator to the surface as described on the product information page. The use of any other product other than Graff Shield, Inc. products will void this warranty.

Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.