

Graffiti Lift

GS-200

Product Description

Graff Shield's GS-200 Lift is a water base clear polymer designed to be removed easily with a power washer. GS-200 Lift is a non-hazardous, environmentally friendly, non-yellowing, non-soluble, biodegradable and cleans up with water.

Primary Uses

Masonry block, split face block, brick, metal, concrete, wood, stucco, siding, vinyl, etc.

Applicaton Equipment

Hand held pump sprayer or airless machine and/or a broom for porous surfaces.

Application

Be sure the surface is clean before applying GS-200 Graffiti Lift. Apply GS-200 Graffiti Lift over GS-100 Graffiti Deterrent by spraying material onto the wall and evenly spreading the material with a broom. When applying this product on signs, brush the material onto the surface. A second coat may be needed to ensure graffiti can be easily removed from the surface.

Coverage Rate

Porous surfaces: (split face block) 250 – 350 square feet per gallon, two coats may be required.

Smooth surfaces: 300 – 400 square feet per gallon.

Packaging

1 Gallon Jug, 5 Gallon Bucket and 55 Gallon Drum.

Caution

This product may cause burns upon prolonged exposure. Harmful if swallowed. In case of contact with eyes or skin, flush with water for 15 minutes and obtain medial attention. Before using this material, read material safety data sheets. Always wear protective clothing and eye protection when using GS-200. Wash your hands after using product. Keep away from children.

First Aid

If ingested, seek medical attention immediately. In case of eye contact, flush with water for 15 minutes. In case of skin contact, wash thoroughly with soap and water. If irritation occurs, seek medical attention.

Warranty

Graff Shield, Inc. warranties that this product is blended to the highest quality. This warranty is only for replacement of material and only if the material that was applied was documented by either a Graff Shield, Inc. representative and/or by an agent or certified applicator of Graff Shield, Inc. products. This can also be done by video taping the installation.

The Graff Shield, Inc. anti-graffiti system must be applied by using GS-100 Graffiti Deterrent in conjunction with GS-200 Graffiti Lift at a rate of 300 square feet per gallon. Every time graffiti is removed, an additional coat of GS-200 Graffiti Lift **must** be re-applied for this warranty be valid. To remove graffiti markings, apply GS-300 Graffiti Eliminator to the surface as described on the product information page. The use of any other product other than Graff Shield, Inc. products will void this warranty.

Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.