

Wall Stamp W-8300

Product Description

Simulated stone without the simulated look! **Americrete Wall Stamp** is a lightweight Portland cement based product designed to be applied to vertical surfaces to achieve the appearance of stone, rock, etc. The special blend of cement and aggregate allows **W-8000 Wall Stamp** to be applied to any surface without wire mesh. It can be applied over block, brick, wood, drywall, painted or unpainted concrete surfaces. It can change the appearance of any interior or exterior surface. This product can be applied over any sound substrate such as plywood, masonry retaining walls, foam, etc. Reduces heat transfer through walls and gives the appearance of real stone at a fraction of the price. For application, see specification A-90,000.

Coverage Rate

W-8000 Wall Stamp Primer 300 to 400 sq. ft. per gallon, depending upon the porosity of the surface.

W-8300 Wall Stamp Cement will receive approx. 25 feet per bag depending upon application process.

Primary Uses

Used to simulate stone looks on vertical surfaces.

Lightweight

Cost effective vs. simulated stone

Heat, sound, water resistant

Durable

Natural looking

Typical Applications

Masonry walls

Retaining walls

Fireplaces

Exterior walls

Water features

BBQ enclosures

Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.